

# LAND CORNER RECORDATION CERTIFICATE <sup>F</sup>

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER

2 PG 345

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>7</u> T. <u>1</u> N. R. <u>1</u> E.		C-4
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, S., R. _____, W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, S., R. _____, W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

FILED

FEB 13 9 04 AM '73

REGISTER OF DEEDS

*Ernie M. Lewis*  
INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Fred N. White do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on December 18 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent-restoration:

Original Corner & Witnesses Obliterated.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found Boat Spike presumed to have been set by ICRC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Boat Spike

2" Steel Street Sign	N20°30'E	72.93'
Anchor Pole	N55°00'E	98.72'
Telephone Pole	S18°00'W	83.80'


SIGNED BY Fred N. White DATE 12-18-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 12034

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER **2 PG 347**

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>7</u> T. <u>1</u> N. <u>1</u> E.	W. R. <u>1</u> W.	C-5
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. S., R. _____, E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. S., R. _____, E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

**FILED**

**FEB 13 9 04 AM '73**

**REGISTER OF DEEDS**  
*Carroll M. Lewis*  
**INGHAM COUNTY, MICH.**

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Fred N. White do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on December 18 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

**Original Corner & Witnesses Obliterated.**

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

**Found Boat Spike presumed to have been set by ICRC**


C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**Boat Spike**

20" Cherry	N65°00'E	25.87'
20" Maple	East	56.40'
Anchor Post	West	27.33'

SIGNED BY *Fred N. White* DATE 12-19-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 12034



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_